

# Package ‘pbapply’

August 18, 2020

**Type** Package

**Title** Adding Progress Bar to ‘\*apply’ Functions

**Version** 1.4-3

**Date** 2020-08-11

**Author** Peter Solymos [aut, cre], Zygmunt Zawadzki [aut]

**Maintainer** Peter Solymos <solymos@ualberta.ca>

**Description** A lightweight package that adds progress bar to vectorized R functions (\*apply). The implementation can easily be added to functions where showing the progress is useful (e.g. bootstrap). The type and style of the progress bar (with percentages or remaining time) can be set through options. Supports several parallel processing backends.

**Depends** R (>= 3.2.0)

**Imports** parallel

**License** GPL-2

**URL** <https://github.com/psolymos/pbapply>

**BugReports** <https://github.com/psolymos/pbapply/issues>

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2020-08-18 07:20:02 UTC

## R topics documented:

pbapply . . . . .	2
pboptions . . . . .	8
splitpb . . . . .	10
timerProgressBar . . . . .	12

<b>Index</b>	<b>15</b>
--------------	-----------

---

 pbapply

 Adding Progress Bar to '\*apply' Functions
 

---

### Description

Adding progress bar to \*apply functions, possibly leveraging parallel processing.

### Usage

```
pblapply(X, FUN, ..., cl = NULL)
```

```
pbapply(X, MARGIN, FUN, ..., cl = NULL)
```

```
pbsapply(X, FUN, ..., simplify = TRUE, USE.NAMES = TRUE, cl = NULL)
```

```
pbreplicate(n, expr, simplify = "array", cl = NULL)
```

```
pbmapply(FUN, ..., MoreArgs = NULL, SIMPLIFY = TRUE, USE.NAMES = TRUE)
```

```
pbtapply(X, INDEX, FUN = NULL, ..., default = NA, simplify = TRUE, cl = NULL)
```

### Arguments

X	For pbsapply and pblapply, a vector (atomic or list) or an expressions vector (other objects including classed objects will be coerced by <code>as.list()</code> .) For pbapply an array, including a matrix. For pbtapply an R object for which a <code>split</code> method exists. Typically vector-like, allowing subsetting with <code>[</code> .
MARGIN	A vector giving the subscripts which the function will be applied over. 1 indicates rows, 2 indicates columns, <code>c(1, 2)</code> indicates rows and columns.
FUN	The function to be applied to each element of X: see <code>apply</code> , <code>sapply</code> , and <code>lapply</code> . In the case of functions like <code>+</code> , <code>%*%</code> , etc., the function name must be backquoted or quoted. If FUN is NULL, pbtapply returns a vector which can be used to subscript the multi-way array pbtapply normally produces.
...	Optional arguments to FUN.
simplify, SIMPLIFY	Logical; should the result be simplified to a vector or matrix if possible? pbtapply returns an array of mode "list" (in other words, a list with a dim attribute) when FALSE; if TRUE (the default), then if FUN always returns a scalar, pbtapply returns an array with the mode of the scalar.
USE.NAMES	Logical; if TRUE and if X is character, use X as names for the result unless it had names already.
n	Number of replications.
expr	Expression (language object, usually a call) to evaluate repeatedly.

c1	A cluster object created by <code>makeCluster</code> , or an integer to indicate number of child-processes (integer values are ignored on Windows) for parallel evaluations (see Details on performance).
MoreArgs	a list of other arguments to FUN.
INDEX	a <code>list</code> of one or more <code>factor</code> s, each of same length as X. The elements are coerced to factors by <code>as.factor</code> .
default	(only in the case of simplification to an array) the value with which the array is initialized as <code>array(default, dim = .)</code> . Before R 3.4.0, this was hard coded to <code>array()</code> 's default NA. If it is NA (the default), the missing value of the answer type, e.g. <code>NA_real_</code> , is chosen ( <code>as.raw(0)</code> for "raw"). In a numerical case, it may be set, e.g., to <code>FUN(integer(0))</code> , e.g., in the case of <code>FUN = sum</code> to 0 or 0L.

## Details

The behaviour of the progress bar is controlled by the option type in `pboptions`, it can take values `c("txt", "win", "tk", "none", )` on Windows, and `c("txt", "tk", "none", )` on Unix systems.

Other options have elements that are arguments used in the functions `timerProgressBar`, `txtProgressBar`, and `tkProgressBar`. See `pboptions` for how to conveniently set these.

Parallel processing can be enabled through the `c1` argument. `parLapply` is called when `c1` is a 'cluster' object, `mclapply` is called when `c1` is an integer. Showing the progress bar increases the communication overhead between the main process and nodes / child processes compared to the parallel equivalents of the functions without the progress bar. The functions fall back to their original equivalents when the progress bar is disabled (i.e. `getOption("pboptions")$type == "none"` or `dopb()` is FALSE). This is the default when `interactive()` is FALSE (i.e. called from command line R script).

When doing parallel processing, other objects might need to be pushed to the workers, and random numbers must be handled with care (see Examples).

Updating the progress bar with `mclapply` can be slightly slower compared to using a Fork cluster (i.e. calling `makeForkCluster`). Care must be taken to set appropriate random numbers in this case.

## Value

Similar to the value returned by the standard `*apply` functions.

A progress bar is showed as a side effect.

## Note

Progress bar can add an overhead to the computation.

## Author(s)

Peter Solymos <solymos@ualberta.ca>

**See Also**

Progress bars used in the functions: [txtProgressBar](#), [tkProgressBar](#), [timerProgressBar](#)

Sequential \*apply functions: [apply](#), [sapply](#), [lapply](#), [replicate](#), [mapply](#), [tapply](#)

Parallel \*apply functions from package 'parallel': [parLapply](#), [mclapply](#).

Setting the options: [pboptions](#)

Conveniently add progress bar to for-like loops: [startpb](#), [setpb](#), [getpb](#), [closepb](#)

**Examples**

```
## --- simple linear model simulation ---
set.seed(1234)
n <- 200
x <- rnorm(n)
y <- rnorm(n, crossprod(t(model.matrix(~ x)), c(0, 1)), sd = 0.5)
d <- data.frame(y, x)
## model fitting and bootstrap
mod <- lm(y ~ x, d)
ndat <- model.frame(mod)
B <- 100
bid <- sapply(1:B, function(i) sample(nrow(ndat), nrow(ndat), TRUE))
fun <- function(z) {
  if (missing(z))
    z <- sample(nrow(ndat), nrow(ndat), TRUE)
  coef(lm(mod$call$formula, data=ndat[z,]))
}

## standard '*apply' functions
system.time(res1 <- lapply(1:B, function(i) fun(bid[,i])))
system.time(res2 <- sapply(1:B, function(i) fun(bid[,i])))
system.time(res3 <- apply(bid, 2, fun))
system.time(res4 <- replicate(B, fun()))

## 'pb*apply' functions
## try different settings:
## "none", "txt", "tk", "win", "timer"
op <- pboptions(type = "timer") # default
system.time(res1pb <- pblapply(1:B, function(i) fun(bid[,i])))
pboptions(op)

pboptions(type = "txt")
system.time(res2pb <- pbsapply(1:B, function(i) fun(bid[,i])))
pboptions(op)

pboptions(type = "txt", style = 1, char = "=")
system.time(res3pb <- pbapply(bid, 2, fun))
pboptions(op)

pboptions(type = "txt", char = ":")
system.time(res4pb <- pbreplicate(B, fun()))
pboptions(op)
```

```

## Not run:
## parallel evaluation using the parallel package
## (n = 2000 and B = 1000 will give visible timing differences)

library(parallel)
cl <- makeCluster(2L)
clusterExport(cl, c("fun", "mod", "ndat", "bid"))

## parallel with no progress bar: snow type cluster
## (RNG is set in the main process to define the object bid)
system.time(res1cl <- parLapply(cl = cl, 1:B, function(i) fun(bid[,i])))
system.time(res2cl <- parSapply(cl = cl, 1:B, function(i) fun(bid[,i])))
system.time(res3cl <- parApply(cl, bid, 2, fun))

## parallel with progress bar: snow type cluster
## (RNG is set in the main process to define the object bid)
system.time(res1pbcl <- pblapply(1:B, function(i) fun(bid[,i]), cl = cl))
system.time(res2pbcl <- pbsapply(1:B, function(i) fun(bid[,i]), cl = cl))
## (RNG needs to be set when not using bid)
parallel::clusterSetRNGStream(cl, iseed = 0L)
system.time(res4pbcl <- pbreplicate(B, fun(), cl = cl))
system.time(res3pbcl <- pbapply(bid, 2, fun, cl = cl))

stopCluster(cl)

if (.Platform$OS.type != "windows") {
  ## parallel with no progress bar: multicore type forking
  ## (mc.set.seed = TRUE in parallel::mclapply by default)
  system.time(res2mc <- mclapply(1:B, function(i) fun(bid[,i]), mc.cores = 2L))
  ## parallel with progress bar: multicore type forking
  ## (mc.set.seed = TRUE in parallel::mclapply by default)
  system.time(res1pbmc <- pblapply(1:B, function(i) fun(bid[,i]), cl = 2L))
  system.time(res2pbmc <- pbsapply(1:B, function(i) fun(bid[,i]), cl = 2L))
  system.time(res4pbmc <- pbreplicate(B, fun(), cl = 2L))
}

## End(Not run)

## --- Examples taken from standard '*apply' functions ---

## --- sapply, lapply, and replicate ---

require(stats); require(graphics)

x <- list(a = 1:10, beta = exp(-3:3), logic = c(TRUE,FALSE,FALSE,TRUE))
# compute the list mean for each list element
pblapply(x, mean)
# median and quartiles for each list element
pblapply(x, quantile, probs = 1:3/4)
pbsapply(x, quantile)
i39 <- sapply(3:9, seq) # list of vectors
pbsapply(i39, fivenum)

```

```

## sapply(*, "array") -- artificial example
(v <- structure(10*(5:8), names = LETTERS[1:4]))
f2 <- function(x, y) outer(rep(x, length.out = 3), y)
(a2 <- pbsapply(v, f2, y = 2*(1:5), simplify = "array"))

hist(pbreplicate(100, mean(rexp(10))))

## use of replicate() with parameters:
foo <- function(x = 1, y = 2) c(x, y)
# does not work: bar <- function(n, ...) replicate(n, foo(...))
bar <- function(n, x) pbreplicate(n, foo(x = x))
bar(5, x = 3)

## --- apply ---

## Compute row and column sums for a matrix:
x <- cbind(x1 = 3, x2 = c(4:1, 2:5))
dimnames(x)[[1]] <- letters[1:8]
pbapply(x, 2, mean, trim = .2)
col.sums <- pbapply(x, 2, sum)
row.sums <- pbapply(x, 1, sum)
rbind(cbind(x, Rtot = row.sums), Ctot = c(col.sums, sum(col.sums)))

stopifnot( pbapply(x, 2, is.vector))

## Sort the columns of a matrix
pbapply(x, 2, sort)

## keeping named dimnames
names(dimnames(x)) <- c("row", "col")
x3 <- array(x, dim = c(dim(x),3),
           dimnames = c(dimnames(x), list(C = paste0("cop.",1:3))))
identical(x, pbapply(x, 2, identity))
identical(x3, pbapply(x3, 2:3, identity))

##- function with extra args:
cave <- function(x, c1, c2) c(mean(x[c1]), mean(x[c2]))
pbapply(x, 1, cave, c1 = "x1", c2 = c("x1", "x2"))

ma <- matrix(c(1:4, 1, 6:8), nrow = 2)
ma
pbapply(ma, 1, table) #--> a list of length 2
pbapply(ma, 1, stats::quantile) # 5 x n matrix with rownames

stopifnot(dim(ma) == dim(pbapply(ma, 1:2, sum)))

## Example with different lengths for each call
z <- array(1:24, dim = 2:4)
zseq <- pbapply(z, 1:2, function(x) seq_len(max(x)))
zseq      ## a 2 x 3 matrix
typeof(zseq) ## list
dim(zseq) ## 2 3

```

```

zseq[1,]
pbapply(z, 3, function(x) seq_len(max(x)))
# a list without a dim attribute

## --- mapply ---

pbmapply(rep, 1:4, 4:1)
pbmapply(rep, times = 1:4, x = 4:1)
pbmapply(rep, times = 1:4, MoreArgs = list(x = 42))
pbmapply(function(x, y) seq_len(x) + y,
          c(a = 1, b = 2, c = 3), # names from first
          c(A = 10, B = 0, C = -10))
word <- function(C, k) paste(rep.int(C, k), collapse = "")
utils::str(pbmapply(word, LETTERS[1:6], 6:1, SIMPLIFY = FALSE))

## --- tapply ---

require(stats)
groups <- as.factor(rbinom(32, n = 5, prob = 0.4))
pbtapply(groups, groups, length) #- is almost the same as
table(groups)

## contingency table from data.frame : array with named dimnames
pbtapply(warpbreaks$breaks, warpbreaks[,-1], sum)
pbtapply(warpbreaks$breaks, warpbreaks[, 3, drop = FALSE], sum)

n <- 17; fac <- factor(rep_len(1:3, n), levels = 1:5)
table(fac)
pbtapply(1:n, fac, sum)
pbtapply(1:n, fac, sum, default = 0) # maybe more desirable
pbtapply(1:n, fac, sum, simplify = FALSE)
pbtapply(1:n, fac, range)
pbtapply(1:n, fac, quantile)
pbtapply(1:n, fac, length) ## NA's
pbtapply(1:n, fac, length, default = 0) # == table(fac)

## example of ... argument: find quarterly means
pbtapply(presidents, cycle(presidents), mean, na.rm = TRUE)

ind <- list(c(1, 2, 2), c("A", "A", "B"))
table(ind)
pbtapply(1:3, ind) #-> the split vector
pbtapply(1:3, ind, sum)

## Some assertions (not held by all patch proposals):
nq <- names(quantile(1:5))
stopifnot(
  identical(pbtapply(1:3, ind), c(1L, 2L, 4L)),
  identical(pbtapply(1:3, ind, sum),
            matrix(c(1L, 2L, NA, 3L), 2, dimnames = list(c("1", "2"), c("A", "B")))),
  identical(pbtapply(1:n, fac, quantile)[-1],
            array(list(`2` = structure(c(2, 5.75, 9.5, 13.25, 17), .Names = nq),
                          `3` = structure(c(3, 6, 9, 12, 15), .Names = nq),

```

```
`4` = NULL, `5` = NULL), dim=4, dimnames=list(as.character(2:5))))
```

---

pboptions

*Creating Progress Bar and Setting Options*

---

## Description

Creating progress bar and setting options.

## Usage

```
pboptions(...)
startpb(min = 0, max = 1)
setpb(pb, value)
getpb(pb)
closepb(pb)
dopb()
pbtypes()
```

## Arguments

...	Arguments in tag = value form, or a list of tagged values. The tags must come from the parameters described below.
pb	A progress bar object created by startpb.
min, max	Finite numeric values for the extremes of the progress bar. Must have min < max.
value	New value for the progress bar.

## Details

pboptions is a convenient way of handling options related to progress bar.

Other functions can be used for conveniently adding progress bar to for-like loops (see Examples).

## Value

When parameters are set by pboptions, their former values are returned in an invisible named list. Such a list can be passed as an argument to pboptions to restore the parameter values. Tags are the following:

type	Type of the progress bar: timer ("timer"), text ("txt"), Windows ("win"), TclTk ("tk"), or none ("none"). Default value is "timer" progress bar with estimated remaining time when in interactive mode, and "none" otherwise. See pbtypes() for available progress bar types depending on operating system.
char	The character (or character string) to form the progress bar. Default value is "+".
txt.width	The width of the text based progress bar, as a multiple of the width of char. If NA, the number of characters is that which fits into getOption("width"). Default value is 50.



<code>gui.width</code>	The width of the GUI based progress bar in pixels: the dialogue box will be 40 pixels wider (plus frame). Default value is 300.
<code>style</code>	The style of the bar, see <a href="#">txtProgressBar</a> and <a href="#">timerProgressBar</a> . Default value is 3.
<code>initial</code>	Initial value for the progress bar. Default value is 0.
<code>title</code>	Character string giving the window title on the GUI dialogue box. Default value is "R progress bar".
<code>label</code>	Character string giving the window label on the GUI dialogue box. Default value is "".
<code>nout</code>	Integer, the maximum number of times the progress bar is updated. The default value is 100. Smaller value minimizes the running time overhead related to updating the progress bar. This can be especially important for forking type parallel runs.
<code>min_time</code>	Minimum time in seconds. <a href="#">timerProgressBar</a> output is printed only if estimated completion time is higher than this value. The default value is 0.
<code>use_lb</code>	Switch for using load balancing when running in parallel clusters. The default value is FALSE.

For `startpb` a progress bar object.

For `getpb` and `setpb`, a length-one numeric vector giving the previous value (invisibly for `setpb`). The return value is NULL if the progress bar is turned off by `getOption("pboptions")$type` ("none" or NULL value).

`dopb` returns a logical value if progress bar is to be shown based on the option `getOption("pboptions")$type`. It is FALSE if the type of progress bar is "none" or NULL.

For `closepb` closes the connection for the progress bar.

`pbtypes` prints the available progress bar types depending on the operating system (i.e. "win" available on Windows only).

### Author(s)

Peter Solymos <solymos@ualberta.ca>

### See Also

Progress bars used in the functions: [timerProgressBar](#), [txtProgressBar](#), [tkProgressBar](#)

### Examples

```
## increase sluggishness to admire the progress bar longer
sluggishness <- 0.01

## for loop
fun1 <- function() {
  pb <- startpb(0, 10)
  on.exit(closepb(pb))
  for (i in 1:10) {
    Sys.sleep(sluggishness)
  }
}
```

```

        setpb(pb, i)
      }
      invisible(NULL)
    }
    ## while loop
    fun2 <- function() {
      pb <- startpb(0, 10-1)
      on.exit(closepb(pb))
      i <- 1
      while (i < 10) {
        Sys.sleep(sluggishness)
        setpb(pb, i)
        i <- i + 1
      }
      invisible(NULL)
    }
    ## using original settings
    fun1()
    ## resetting pboptions
    opb <- pboptions(style = 1, char = ">")
    ## check new settings
    getOption("pboptions")
    ## running again with new settings
    fun2()
    ## resetting original
    pboptions(opb)
    ## check reset
    getOption("pboptions")
    fun1()

    ## dealing with nested progress bars
    ## when only one the 1st one is needed
    f <- function(x) Sys.sleep(sluggishness)
    g <- function(x) pblapply(1:10, f)
    tmp <- lapply(1:10, g) # undesirable
    ## here is the desirable solution
    h <- function(x) {
      opb <- pboptions(type="none")
      on.exit(pboptions(opb))
      pblapply(1:10, f)
    }
    tmp <- pblapply(1:10, h)

    ## list available pb types
    pbtypes()

```

**Description**

Divides up  $1:nx$  into approximately equal sizes ( $nc1$ ) as a way to allocate tasks to nodes in a cluster repeatedly while updating a progress bar.

**Usage**

```
splitpb(nx, nc1, nout = NULL)
```

**Arguments**

<code>nx</code>	Number of tasks.
<code>nc1</code>	Number of cluster nodes.
<code>nout</code>	Integer, maximum number of partitions in the output (must be $> 0$ ).

**Value**

A list of length  $\min(\text{nout}, \text{ceiling}(nx / nc1))$ , each element being an integer vector of length  $nc1 * k$  or less, where  $k$  is a tuning parameter constrained by the other arguments ( $k = \max(1L, \text{ceiling}(\text{ceiling}(nx / nc1) / \text{nout}))$  and  $k = 1$  if  $\text{nout} = \text{NULL}$ ).

**Author(s)**

Peter Solymos <solymos@ualberta.ca>

**See Also**

Parallel usage of [pbapply](#) and related functions.

**Examples**

```
## define 1 job / worker at a time and repeat
splitpb(10, 4)
## compare this to the no-progress-bar split
## that defines all the jobs / worker up front
parallel::splitIndices(10, 4)

## cap the length of the output
splitpb(20, 2, nout = NULL)
splitpb(20, 2, nout = 5)
```

---

timerProgressBar      *Timer Progress Bar*

---

## Description

Text progress bar with timer in the R console.

## Usage

```
timerProgressBar(min = 0, max = 1, initial = 0, char = "=",
  width = NA, title, label, style = 1, file = "", min_time = 0)
getTimerProgressBar(pb)
setTimerProgressBar(pb, value, title = NULL, label = NULL)
getTimeAsString(time)
```

## Arguments

min, max	(finite) numeric values for the extremes of the progress bar. Must have min < max.
initial, value	initial or new value for the progress bar. See Details for what happens with invalid values.
char	the character (or character string) to form the progress bar. If number of characters is >1, it is silently stripped to length 1 unless style is 5 or 6 (see Details).
width	the width of the progress bar, as a multiple of the width of char. If NA, the default, the number of characters is that which fits into <code>getOption("width")</code> .
style	the style taking values between 1 and 6. 1: progress bar with elapsed and remaining time, remaining percentage is indicated by spaces between pipes (default for this function), 2: throbber with elapsed and remaining time, 3: progress bar with remaining time printing elapsed time at the end, remaining percentage is indicated by spaces between pipes (default for style option in <a href="#">pboptions</a> ), 4: throbber with remaining time printing elapsed time at the end, 5: progress bar with elapsed and remaining time with more flexible styling (see Details and Examples), 6: progress bar with remaining time printing elapsed time at the end with more flexible styling (see Details and Examples).
file	an open connection object or "" which indicates the console.
min_time	numeric, minimum processing time (in seconds) required to show a progress bar.
pb	an object of class "timerProgressBar".
title, label	ignored, for compatibility with other progress bars.
time	numeric of length 1, time in seconds.

**Details**

timerProgressBar will display a progress bar on the R console (or a connection) via a text representation.

setTimerProgressBar will update the value. Missing (NA) and out-of-range values of value will be (silently) ignored. (Such values of initial cause the progress bar not to be displayed until a valid value is set.)

The progress bar should be closed when finished with: this outputs the final newline character (see [closepb](#)).

If style is 5 or 6, it is possible to define up to 4 characters for the char argument (as a single string) for the left end, elapsed portion, remaining portion, and right end of the progress bar (|=| by default). Remaining portion cannot be the same as the elapsed portion (space is used for remaining in such cases). If 1 character is defined, it is taken for the elapsed portion. If 2-4 characters are defined, those are interpreted in sequence (left and right end being the same when 2-3 characters defined), see Examples.

getTimeAsString converts time in seconds into ~HHh MMm SSs format to be printed by timerProgressBar.

**Value**

For timerProgressBar an object of class "timerProgressBar" inheriting from "txtProgressBar".

For getTimeProgressBar and setTimerProgressBar, a length-one numeric vector giving the previous value (invisibly for setTimerProgressBar).

getTimeAsString returns time in ~HHh MMm SSs format as character. Returns "calculating" when time=NULL.

**Author(s)**

Zygmunt Zawadzki <zawadzki@zawadzki.com>

Peter Solymos <solymos@ualberta.ca>

**See Also**

The timerProgressBar implementation follows closely the code of [txtProgressBar](#).

**Examples**

```
## increase sluggishness to admire the progress bar longer
sluggishness <- 0.02

test_fun <- function(...)
{
  pb <- timerProgressBar(...)
  on.exit(close(pb))
  for (i in seq(0, 1, 0.05)) {
    Sys.sleep(sluggishness)
    setTimerProgressBar(pb, i)
  }
  invisible(NULL)
}
```

```

## check the different styles
test_fun(width = 35, char = "+", style = 1)
test_fun(style = 2)
test_fun(width = 50, char = ".", style = 3)
test_fun(style = 4)
test_fun(width = 35, char = "[=-]", style = 5)
test_fun(width = 50, char = "{*.*}", style = 6)

## no bar only percent and elapsed
test_fun(width = 0, char = " ", style = 6)

## this should produce a progress bar based on min_time
(elapsed <- system.time(test_fun(width = 35, min_time = 0))["elapsed"])
## this should not produce a progress bar based on min_time
system.time(test_fun(min_time = 2 * elapsed))["elapsed"]

## time formatting
getTimeAsString(NULL)
getTimeAsString(15)
getTimeAsString(65)
getTimeAsString(6005)

## example usage of getTimeAsString, use sluggishness <- 1
n <- 10
t0 <- proc.time()[3]
ETA <- NULL
for (i in seq_len(n)) {
  cat(i, "/", n, "- ETA:", getTimeAsString(ETA))
  flush.console()
  Sys.sleep(sluggishness)
  dt <- proc.time()[3] - t0
  cat(" - elapsed:", getTimeAsString(dt), "\n")
  ETA <- (n - i) * dt / i
}

```

# Index

- \* **IO**
  - pboptions, 8
- \* **manip**
  - pbapply, 2
- \* **utilities**
  - pbapply, 2
  - pboptions, 8
  - splitpb, 10
  - timerProgressBar, 12
- [, 2
- apply, 2, 4
- array, 3
- as.factor, 3
- as.list, 2
- as.raw, 3
  
- closepb, 4, 13
- closepb (pboptions), 8
  
- dopb (pboptions), 8
  
- factor, 3
  
- getpb, 4
- getpb (pboptions), 8
- getTimeAsString (timerProgressBar), 12
- getTimerProgressBar (timerProgressBar), 12
  
- lapply, 2, 4
- list, 3
  
- makeCluster, 3
- makeForkCluster, 3
- mapply, 4
- mclapply, 3, 4
  
- NA\_real\_, 3
  
- parLapply, 3, 4
  
- pbapply, 2, 11
- pblapply (pbapply), 2
- pbmapply (pbapply), 2
- pboptions, 3, 4, 8, 12
- pbreplicate (pbapply), 2
- pbsapply (pbapply), 2
- pbtapply (pbapply), 2
- pbtypes (pboptions), 8
  
- replicate, 4
  
- sapply, 2, 4
- setpb, 4
- setpb (pboptions), 8
- setTimerProgressBar (timerProgressBar), 12
  
- split, 2
- splitpb, 10
- startpb, 4
- startpb (pboptions), 8
  
- tapply, 4
- timerProgressBar, 3, 4, 9, 12
- tkProgressBar, 3, 4, 9
- txtProgressBar, 3, 4, 9, 13